

Implementing Beaver Dam Analogs in

Atlanta's Nancy Creek Watershed

Glen Behrend, P.E. – City of Atlanta Ty Smith, P.E. – Hazen & Sawyer



Mikita K. Browning, Interim Commissioner Department of Watershed Management 9/30/2020 1









Online Pond, Forested Watershed

Dam Breached, Increased Urban Development Present Conditions, Nature Preserve



Historic Habitat Precedent

Atlanta Beaver Dam Analogs





Implement 8.7 acres of wetland restoration via Beaver Dam Analogs (BDAs) in order to:

- Reduce urban sediment pollution to Nancy Creek
- Enhance riparian and aquatic habitat within the Preserve
- Increase flood attenuation through floodplain reconnection
- Reduced immediate site impacts during construction













Key Steps

- 1. Base Mapping
- 2. Historic Aerial Imagery Review
- 3. Field Investigation & Characterization
- 4. Remote Monitoring Sensor Deployment
- 5. "Plan Set" Development
- 6. Permitting Agency Coordination
- 7. Construction & Field Engineering*



Structural Elements

Atlanta Beaver Dam Analogs





Has this been done before?

Atlanta Beaver Dam Analogs





- Grant from GAEPD for US EPA 319(h)
- City of Atlanta DWM Municipal Option Sales Tax (MOST) Match
- In kind donation
 - Blue Heron Nature Preserve Staff and Volunteers
 - University and Foundation Partners

Project Identification, Estimated Construction Fee: ~\$1,300,000 Selected Approach, Approximate Construction Fee: ~\$155,000



- NWP27 Permit, Savannah District – authorization concurrence received
- Permits Not Needed:
 - City of Atlanta Land
 Disturbance Permit
 - GA EPD Buffer Variance Permit
 - NPDES Construction Permit

Not a land disturbing activity





Remote Sensors Deployment

Water Depth, Dissolved Oxygen, Conductivity, Temperature, Light



Visual Monitoring Stations

Time-lapse 360-Degree Imagery



Aquatic Habitat & Geomorphic Surveys











BDA Construction Process

Atlanta Beaver Dam Analogs

- 1. Install post material via **pneumatic** driver.
- 2. Weave & pack material to **desired** crest elevation.
- 3. Plug upstream base with mud & substrate to prevent leaks.
- 4. Repeat Steps 2 & 3 in 6" to 12" lifts to achieve desired crest elevation.
- 5. Install downstream scour mattress.
- 6. Pack again. 😊













Atlanta Beaver Dam Analogs



Sharpening posts can be a bigger challenge than expected



Atlanta Beaver Dam Analogs



Ensure that each layer is properly woven, packed, and plugged.

Field Engineering recommended!



Atlanta Beaver Dam Analogs



Branches were not adequately attached to the bank contributing to end cut wash out.



Atlanta Beaver Dam Analogs



Holes can lead to undermining posts and dam failure.





Mounding with gradual increase can limit under cut forces which reduces holes and post failure potential.



Lessons Learned, Human Element

Atlanta Beaver Dam Analogs



Unintentional movement of boardwalk Boardwalk construction was not coordinated with BDAs.



On-going maintenance is necessary

- Trash removal
- Maintain desired height
- Correct/fill damage, if needed
- Ideally, beaver will adopt



Public and Stakeholder Outreach

- Holistic thinking and strategic watershed management is crucial to realizing the benefits of stream uplift in more urbanized settings
 - Recognize and get concurrence from decision makers
 - Educate neighbors



Urban Ecology Framework

Atlanta Beaver Dam Analogs



Atlanta is committed to urban ecology, tree canopy protection, & resilience.









